



## DP100 DP150 Diesel Clean Water Pump 13.5L Tank 3 Diesel Water Pump

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



### Product Specification

- Type: Diesel Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on [dieselenginepumps.com](http://dieselenginepumps.com)

## Product Description

### GETDP50 GETDP80 GETDP100 GETDP150 Diesel Pump For Clean Water

GETDP50, GETDP80, GETDP100, and GETDP150, are examples of diesel pumps designed for pumping clean water. These pumps are commonly used in various applications where water needs to be moved efficiently and reliably. Here are some key features and specifications of these diesel pumps:

**GETDP50 Diesel Pump for Clean Water:**

Flow Rate: Typically around 50 cubic meters per hour (m<sup>3</sup>/h)

Head (Vertical Lift): Generally up to 25 meters

Engine Power: Typically ranges from 3 to 6 horsepower (hp)

Fuel Type: Diesel

Pump Type: Centrifugal pump or self-priming pump

Application: Suitable for smaller water pumping tasks, such as irrigation, drainage, and small construction sites.

**GETDP80 Diesel Pump for Clean Water:**

Flow Rate: Typically around 80 m<sup>3</sup>/h

Head (Vertical Lift): Generally up to 30 meters

Engine Power: Typically ranges from 6 to 13 hp

Fuel Type: Diesel

Pump Type: Centrifugal pump or self-priming pump

Application: Suitable for medium-sized water pumping needs, including agricultural irrigation, dewatering, and municipal water supply.

**GETDP100 Diesel Pump for Clean Water:**

Flow Rate: Typically around 100 m<sup>3</sup>/h

Head (Vertical Lift): Generally up to 35 meters

Engine Power: Typically ranges from 13 to 20 hp

Fuel Type: Diesel

Pump Type: Centrifugal pump or self-priming pump

Application: Suitable for larger water pumping tasks, such as industrial applications, construction sites, and flood control.

**GETDP150 Diesel Pump for Clean Water:**

Flow Rate: Typically around 150 m<sup>3</sup>/h

Head (Vertical Lift): Generally up to 40 meters

Engine Power: Typically ranges from 20 to 40 hp

Fuel Type: Diesel

Pump Type: Centrifugal pump or self-priming pump

Application: Suitable for high-capacity water pumping requirements, such as large-scale irrigation, water transfer, and mining operations.

Type:	Diesel Clean Water Pump	Suction/discharge Port Diameter Mm(inch):	50(2"). 80(3"). 100(4"). 150(6")
Discharge Capacity(m <sup>3</sup> /h):	30 40 110 150	Total Head Lift:	25m 26m 22m 20m
Self-priming Time (s/4m):	80 120 180 180	Max Suction Head:	8m 8m 8m 6m
Rotation Speed (r/min):	3600	Noise Level Db(A)/7m):	85
Overall Dimension(mm):	510x455x640. 560x455x655. 650x470x700. 770x574x785	Dry Weight:	44kg 50kg 71kg 95kg
Engine Model:	GET173F GET178F GET186FA GET192F	Rated Power:	2.8kw 4kw 6.3kw 8.5kw
Fuel Consumption G/kw.h:	288 285 281 281	Displacement (cm <sup>3</sup> ):	247 296 418 498
Starter System:	Recoil Starter	Fuel Tank Capacity:	13.5L

These diesel pumps are designed to be robust, efficient, and suitable for continuous operation. They are often equipped with features such as self-priming capabilities, durable construction, and easy maintenance access. It's important to consider factors like the desired flow rate, head requirements, and specific application needs when selecting a diesel pump for clean water. Always refer to the manufacturer's documentation and consult with a knowledgeable professional to ensure you choose the appropriate pump for your specific requirements.

清水泵 Diesel Pump for Clean Water



参数表 Specifications

	GET100P	GET150P	GET200P	GET250P
产品系列 Type	Diesel water pump	Diesel water pump	Diesel water pump	Diesel water pump
进出口口径 Inlet/Outgoing Port Diameter	mm (in)	50(2")	65(2.5")	100(4")
最大流量 Discharge capacity	m³/h	35	40	115
最大扬程 Max head (ft)	m	35	30	30
额定转速 Rated speed (rpm)	1500	1500	1500	1500
最大转速 Max rotation speed	rpm	3000	3000	3000
重量 Weight (kg)	15	20	35	45
外形尺寸 Overall Dimensions	mm	340*340*340	340*340*340	340*340*340
净重 Dry weight	kg	15	20	35
额定功率 Rated Power	kw	2.2	4	11.5
燃油消耗率 Fuel consumption	g/kwh	200	200	200
噪音 Decibel (dB)	75	80	85	90
冷却方式 Cooling system	Water cooling	Water cooling	Water cooling	Water cooling
最大流量 Max discharge capacity	L	10.5	10.5	10.5
最大扬程 Max head (m)	m	30	30	30

30



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselpumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA