



## 8500E 9500E Open Type Diesel Generator Air Cooled Diesel Engine Generator

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



### Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
- Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
- Rated Voltage (V): 220V Or As Request
- Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel

for more products please visit us on [diesenginepumps.com](http://diesenginepumps.com)

## Product Description

Fuel Efficiency Open Type Diesel Generator GET2500E GET3500E GET6500E GET7500E GET8500E GET9500E

### GET2500E GET3500E GET6500E GET7500E GET8500E GET9500E Open Type Diesel Generator

It's important to consider the noise level and any specific noise regulations or requirements when opting for an open type diesel generator, as they tend to produce more noise compared to enclosed or soundproof models.

**Wide Range of Power Output:** Open type diesel generators are available in a wide range of power outputs, offering flexibility to meet different power demands. They can be used for small-scale residential backup power needs or larger industrial applications requiring higher power capacities.

**Durability and Reliability:** Diesel generators are known for their durability and reliability. They are designed to withstand heavy-duty usage, harsh environmental conditions, and frequent start-ups and shutdowns. This ensures a consistent and dependable power supply in various operating conditions.

**Fuel Efficiency:** Diesel engines are known for their fuel efficiency. Open type diesel generators consume less fuel compared to gasoline-powered generators, resulting in reduced operating costs over time.

**Fuel Availability:** Diesel fuel is widely available and easily accessible in most areas. This makes it convenient to refuel open type diesel generators, especially in remote locations or areas without a stable electrical grid.

**Compatibility with Heavy Loads:** Open type diesel generators are capable of handling heavy electrical loads and sudden peak demands. They provide a stable power supply, making them suitable for applications that require reliable power for machinery, industrial equipment, and other high-power-demand devices.

Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ 730x495x630/ 730x495x655
Working Assorting Weight (kg):	66 83 110 115 120 125
Structure Type:	Open Type
Cylinder No. -bore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 20Ah/ 12V 30Ah
Fuel Tank Capacity (L):	13.5
Rated Frequency:	50hz 60hz
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	53 70 100 105 110 115
Noise Level (7m):	77 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	247 296 418 456 498 531
Compression Ratio:	20:01, 19:01
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	0.75 1.1 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

[illegible]